

# PROTECT C

## SINGLE PHASE IN / OUT UPS SYSTEM

Uninterruptible Power Supply

1-Phase Input; 1-Phase Output

1000 – 10000 VA power supply  
with integrated batteries



### Uninterruptible security for applications in the SMB sector

Real VFI / double conversion online technology suitable for safe supply application-critical consumers in the IT environment such as workstations, servers, storage systems, as well as in the area of sensitive switching and control systems.

The new Protect C models in the performance levels in 1000, 2000 and 3000 VA range represent consistent further development of the well-proven and highly reliable series.

With the lag increased to 0.9, the power factor was taken into account for the demand for higher performance active consumers. The ECO and frequency inverter for operation mode highlights the requirements for a modern versatile UPS.

#### Optimal control and information

"Dual-monitoring" enabled interfaces extend communication opportunities. The universally usable communication slot also allows for the integration of SNMP network interface cards that allow for monitoring and management options, particularly multi-server shutdown. The AEG "CompuWatch" shutdown software is always included.

The multilingual graphical LCD display provides all the important operating states and values that can be stored and retrieved in addition to real-time data storage in plain text.

### Main characteristics

- » VFI topology (online / double conversion) protection against all mains network problems
- » Extremely wide input voltage window of 110 VAC to 300 VAC without stress on the internal battery system and with a stable output voltage
- » ECO and frequency operating voltage possible
- » Expansion slot for SNMP, potential free contacts, remote display
- » Graphic LCD display with interactive multilingual user interface
- » Configuration options (password protected) via the operator terminal
- » Internal hardware data logger with plain text display and date / time stamp
- » Emergency power off on terminal block (potential-free)

<b>Classification VFI SS 111* acc. to IEC 62040-3</b>	C. 1000	C. 2000	C. 3000
<b>Power type rating</b>	1000 VA	2000 VA	3000 VA
	900 W	1800 W	2700 W
<b>Part number (UPS including integrated battery system)</b>	600 002 1234	600 002 1236	600 002 1237
<b>Part number (additional battery pack)</b>	600 001 6106	600 001 6107	
<b>UPS INPUT</b>			
<b>Input voltage</b>	220 VAC / 230 VAC / 240 VAC		
<b>Voltage range without battery mode (load dependent)</b>	110 – 300 VAC		
<b>Frequency (auto selection)</b>	50 Hz / 60 Hz $\pm$ 10 Hz		
<b>Mains current (system reaction)</b>	$\lambda \geq 0.99$ (THDi <5%)		
<b>Current consumption at nominal load (max.) (at 230 VAC incl. max. battery charging current)</b>	4.6 A	8.5 A	12.5 A
<b>UPS OUTPUT</b>			
<b>Rated output voltage (adjustable)</b>	200 VAC / 208 VAC / 220 VAC / 230 VAC (default setting) / 240 VAC $\pm$ 2 %		
<b>Frequency in battery / frequency converter mode</b>	50 Hz / 60 Hz $\pm$ 0.2 Hz		
<b>Nominal output current (at 230 VAC)</b>	4.3 A	8.7 A	13 A
<b>Transfer time at mains outage</b>	0 ms (without interruption)		
<b>Voltage waveform</b>	Sinusoidal, distortion <3 %		
<b>Overload response (double conversion &amp; battery mode)</b>	<110 % for 60 s / 110 % up to <125 % for 30s / 125 % up to 150 % for 10s Subsequent, transfer to bypass mode (if bypass available)		
<b>Crest factor</b>	3 : 1		
<b>Short circuit response</b>	Short circuit proof (3 x I <sub>N</sub> for 100 ms)		
<b>BATTERY</b>			
<b>Type</b>	Sealed, maintenance-free (proprietary brand), integrated		
<b>Rated voltage (linked)</b>	36 VDC	96 VDC	
<b>Battery management</b>	Exhaustive discharge protection / Protection against excess load Automatic battery test (daily, weekly, monthly)		
<b>Charging time (to 90 % rated capacity)</b>	5 h		
<b>COMMUNICATION</b>			
<b>Interfaces (dual monitoring)</b>	RS232, USB, communication slot (can be used parallel with RS232 / USB), input contact for emergency power off		
<b>Shutdown software (on CD)</b>	5 network licenses for all common OS (e.g. Windows, Linux, Mac, Unix)		
<b>User interface / failure indication (acoustic/visual)</b>	3 LED's with traffic light display, detailed indication via LCD display (alarms: at mains failure, overload, battery charging, battery replacement, fan fault data logger – with clear text display incl. Date and time history)		
<b>GENERAL DATA</b>			
<b>Efficiency (ECO mode)</b>	>94 %	>94 %	
<b>Efficiency at nominal load (double conversion mode)</b>	>87%	>88 %	
<b>Audible noise (1 m distance)</b>	$\leq$ 44 dB(A)	$\leq$ 49 dB(A)	
	with intelligent fan speed control and fan monitoring		
<b>Temperature range</b>	0 – 45 %		
<b>Humidity</b>	0 – 95 % (no condensation)		
<b>Operation altitude</b>	Up to 1000 m at nominal load		
<b>EMC conformity</b>	EN 62040-2 Class C1, EN 61000-3-2, EN 61000-3-3		
<b>Product safety</b>	EN 62040-1		
<b>Mains input</b>	IEC 320 C14		IEC 320 C20
<b>Number of outputs</b>	4 x IEC 320 C13	6 x IEC 320 C13	4 x IEC 320 C13
			1 x IEC 320 C19 + terminal
<b>Equipment color</b>	Blackline with silver colored front cover		
<b>Dimensions approx. W x H x D (mm) UPS</b>	145 x 220 x 400	190 x 345 x 460	
<b>Dimensions approx. W x H x D (mm) battery</b>	Integrated (additional battery pack same dimensions as UPS)		
<b>Weight approx. UPS</b>	13 kg	31 kg	
<b>Weight approx. battery</b>	19 kg	52 kg	
<b>Shipment</b>	Mains input cord, 2 device cords, communication cable (USB), management software "CompuWatch" (CD), incl. 5 network licences, operating instructions		
<b>Conformity</b>	CE		

\* excl. ECO / Bypass mode

# PROTECT C. 6000/10000



## High-performance UPS system for IT applications

Thanks to genuine VFI technology (online/double conversion), Protect C is suitable for all critical business applications.

The proven VFI topology of Protect C protects against all network problems as a matter of principle. A sinus-shaped power feed is achieved under all load conditions at the input.

Highly integrated switches and a robust IGBT module reduce the number of electrical connections and components and therefore provide for increased reliability. A Static Bypass Switch (SBS) and/or an automated bypass ensure additional safety in case of overload.

### Maximum control

The bar displays for UPS load and battery capacity, as well as the clear pictogram of the system components provide information on the essential operating conditions.

Data is transmitted through an RS232 interface. With an optional SNMP (PRO) adapter, remote monitoring via a web browser and multi-server shutdown are possible.

The special AEG shutdown software "CompuWatch" is of course included.

### Switchable in parallel

Protect C. 6000 and C. 10000 offer the possibility of parallel operation. Both active redundancy and higher availability are achieved with higher power requirements being taken into account.

Also, the combination of power increase and active redundancy is possible, as up to 3 devices can be switched in parallel.

Protect C meets the highest security and availability requirements and allows for an economical implementation.

## Main characteristics

- » VFI topology (online/double conversion) protects against all network problems
- » Micro processor control/digital signal processors for maximum availability
- » Sinus-shaped power feed (high-frequency pulse width modulation with IGBTs)
- » n+x technology for redundancy and performance increase
- » Extension slot for SNMP, potential-free contacts, remote panel
- » Also available as an S-version with reinforced charging rectifier
- » Space saving design with integrated battery system
- » Integrated fault operation security for manual bypass switch

Classification VFI SS 111 acc. to IEC 62040-3	C. 6000	C. 10000
Power type rating	6000 VA	10000 VA
	4200 W	7000 W
	Parallel connection	Parallel connection
Part number (UPS including integrated battery system)	600 000 5877	600 000 5878
Part number (battery pack)	600 000 5879	600 000 5880
Part number (UPS S-version)	600 000 4340	600 000 4341
<b>UPS INPUT</b>		
Input voltage	220 VAC / 230 VAC / 240 VAC	
Voltage range without battery mode	176 – 276 VAC	
Frequency (auto selection)	50 Hz / 60 Hz $\pm$ 4 Hz	
Mains current (system reaction)	$\lambda \geq 0.98$	
Current consumption at nominal load (max.)	31 A	50 A
<b>UPS OUTPUT</b>		
Rated output voltage (adjustable)	220 VAC / 230 VAC (default) / 240 VAC $\pm$ 1 %	
Frequency in battery mode	50 Hz / 60 Hz $\pm$ 0.1 %	
Output current (at 230 VAC)	26 A	43.4 A
Transfer time at mains outage	0 ms (without interruption)	
Voltage waveform	Sinusoidal, distortion THD <4 %	
Overload response (online operation)	<130 % for 10 min. / 130 % for 1 s Subsequent, transfer to bypass mode	
Crest factor	3 : 1	
Short circuit response	Short circuit proof (3 x I <sub>N</sub> for 140 ms)	
<b>BATTERY</b>		
Type	Sealed, maintenance free, integrated (proprietary brand)	
Rated voltage (linked)	240 VDC	
Overload/deep discharge protection	Yes	
Charging time (to 90 % rated capacity)	7 h	
<b>COMMUNICATION</b>		
Interfaces	RS232 (with status display and data), communications slot for SNMP, potential free relay contact	
Shutdown software (on CD)	5 network licenses for all common OS (e.g. Windows, Linux, Mac)	
Failure indicators (acoustic/visual)	LED display for UPS summary /battery capacity display, status display Indicators for mains failure, overload, battery charging, battery replacement, failure	
<b>GENERAL DATA</b>		
Efficiency AC – AC (at nominal load)	$\geq 90$ %	
Audible noise (1 m distance)	<55 dB(A)	
Operating temperature range	0° – 40°C	
Humidity	0 – 90 % (without condensation)	
Operation altitude	Up to 1000 m at nominal load	
EMC conformity	EN 62040-2 Class C3	
Product safety	EN 62040-1	
Mains input	Secured terminal block	
Consumer outputs	Secured terminal block	
Equipment color	Blackline with silver colored front cover	
Dimensions approx. W x H x D (mm) UPS	260 x 720 x 570	
Dimensions approx. W x H x D (mm) battery	Integrated (not S-version battery pack same dimensions as UPS)	
Weight approx. UPS	90 kg	93 kg
Weight approx. battery	65 kg	68 kg
Shipment	Parallel connection cable, management software "CompuWatch" (CD), communications cable, operating instructions	
Conformity	CE	

AEG PS - Protect C - EN - 11/2017 V3 - Technical data in this document does not contain any binding guarantees or warranties. Content only serves for information purposes and can be modified at any time. We will make binding commitments only upon receipt of concrete enquiries and customer notification of the relevant conditions. Due to the non-binding nature of these terms, we assume liability neither for the accuracy nor completeness of the data provided here. AEG is a registered trademark used under license from AB Electrolux.



## AEG Power Solutions

Approach your local AEG Power Solutions representative for further support. Contact details can be found on:

[www.aegps.com](http://www.aegps.com)

**AEG**  
POWER SOLUTIONS